

SenTec Connectivity to iMDsoft MetaVision®

More vital patient data at a glance

iMDsoft MetaVision

- Displays and stores real-time data from SDM (updated every minute)
- Possibility to duplicate additional data, e.g. pulsation index (PI) and sensor temperature



SenTec connectivity enables the transmission of oxygenation and ventilation monitoring - tcPCO2, tcPO2, SpO2, Pulse Rate (PR), Pulsation Index (PI), Heating Power (HP) - to iMDsoft MetaVision.



to iMDsoft MetaVision®

Required Components	System Requirements	Description
SenTec Digital Monitor (SDM)	Sofware version SMB V08.00/V08.01	Provides noninvasive and continuous real-time monitoring of ventilation and oxygenation
MetaVision	Version 5 or higher	Displays and stores customizable data from SDM. No special system requirements necessary (all Windows versions support MetaVision)
Digi Connect™		Transmits and translates data from SDM to MetaVision
Serial to LAN converter cable 250372-15D		Connects SDM and Digi Connect
Standard LAN cable (RJ45)		Optional connection between Digi Connect and PC/server. Digi Connect also supports connection via WLAN

SenTec Connectivity Support Team

We help you get connected

If you need any support, please contact your local SenTec representative or send an e-mail to connectivity@sentec.com or consult your iMDsoft representative.

Please visit www.sentec.com for more detailed technical and service information.

Your local distributor



Ringstrasse 39 4106 Therwil Switzerland www.sentec.com Tel +41 61 726 97 60 Fax +41 61 726 97 61

Connectivity Support Team +49 381 3677 96127 connectivity@sentec.com



Schiessstraße 55 40549 Düsseldorf Germany www.imd-soft.com Note: This is a global overview and may contain information on products not released in all markets/countries. Information is subject to change without notice. http://www.sentec.com/int/info/legal-disclaimer/