

Vital patient data at a glance



Sentec Connectivity enables the transmission of oxygenation and ventilation monitoring – **tcPCO₂, tcPO₂, SpO₂, Pulse Rate (PR), Pulsation Index (PI), Heating Power (HP)** – to iMDsoft MetaVision®.








Sentec Connectivity iMDsoft MetaVision®

- Displays and stores real-time data from Sentec Digital Monitor (SDM) (updated every minute)
- Possibility to duplicate additional data, e.g. pulsation index (PI) and sensor temperature

Care with
Confidence

Sentec Connectivity

iMDsoft MetaVision®

Required Components	System Requirements	Description
Sentec Digital Monitor (SDM) 	Software Version SMB V08.00 to V08.03	Provides noninvasive and continuous real-time monitoring of ventilation and oxygenation
MetaVision® 	Version 5 or higher	Displays and stores customizable data from SDM. No special system requirements necessary (all Windows versions support MetaVision®)
Digi Connect™ 		Transmits and translates data from SDM to MetaVision®
Serial to LAN converter cable 250372-15D 		Connects SDM and Digi Connect™
Standard LAN cable (RJ45) 		Optional connection between Digi Connect™ and PC/server. Digi Connect™ also supports connection via WLAN

Sentec Connectivity Support Team

Let's connect.

If you need support, please contact your local Sentec representative, send an e-mail to connectivity@sentec.com or consult your iMDsoft representative.

Please visit www.sentec.com for more information.

Your local distributor:

sentec.

Ringstrasse 39
4106 Therwil
Switzerland
www.sentec.com
 Made in Switzerland

Sentec Connectivity Support Team:
Tel +41 61 726 97 60
connectivity@sentec.com

iMDsoft®

Park Atidim, Bldg. 4
POB 58178, Tel Aviv
6158101
Israel
Account-Managers@imd-soft.com

Note: This is a global overview and may contain information on products not released in all markets/countries. Information is subject to change without notice.